

## What is Covered

Product Type	Standard Warranty Terms	No Fault Warranty Protection "NFWP"	No Fault Warranty Gold "NFWP"
<p>Standard</p>	<p>Standard</p>	<p>Standard</p>	<p>Standard</p>
<p>Standard</p>	<p>Standard</p>	<p>Standard</p>	<p>Standard</p>
<p>Standard</p>	<p>Standard</p>	<p>Standard</p>	<p>Standard</p>
<p>Standard</p>	<p>Standard</p>	<p>Standard</p>	<p>Standard</p>
<p>Standard</p>	<p>Standard</p>	<p>Standard</p>	<p>Standard</p>





# INSTALLATION, BREAK-IN PROCEDURES

1. Read the entire manual before starting the engine. 2. Check the oil level and change it if necessary. 3. Check the spark plug gap and adjust it if necessary. 4. Check the air filter and clean it if necessary. 5. Check the fuel filter and replace it if necessary. 6. Check the battery and charge it if necessary. 7. Check the belt tension and adjust it if necessary. 8. Check the cooling system and fill it with water if necessary. 9. Check the exhaust system and clean it if necessary. 10. Check the engine oil and change it if necessary.

## Engines and Cylinder Heads

1. Remove the spark plug and check the gap. 2. Check the oil level and change it if necessary. 3. Check the air filter and clean it if necessary. 4. Check the fuel filter and replace it if necessary. 5. Check the battery and charge it if necessary. 6. Check the belt tension and adjust it if necessary. 7. Check the cooling system and fill it with water if necessary. 8. Check the exhaust system and clean it if necessary. 9. Check the engine oil and change it if necessary. 10. Check the cylinder head and clean it if necessary.

## Initial Startup

1. Check the oil level and change it if necessary. 2. Check the spark plug gap and adjust it if necessary. 3. Check the air filter and clean it if necessary. 4. Check the fuel filter and replace it if necessary. 5. Check the battery and charge it if necessary. 6. Check the belt tension and adjust it if necessary. 7. Check the cooling system and fill it with water if necessary. 8. Check the exhaust system and clean it if necessary. 9. Check the engine oil and change it if necessary. 10. Start the engine and let it run for 5 minutes.

## Break-in Procedures

1. Start the engine and let it run for 5 minutes. 2. Drive the engine at 1500 RPM for 10 minutes. 3. Drive the engine at 2000 RPM for 10 minutes. 4. Drive the engine at 2500 RPM for 10 minutes. 5. Drive the engine at 3000 RPM for 10 minutes. 6. Drive the engine at 3500 RPM for 10 minutes. 7. Drive the engine at 4000 RPM for 10 minutes. 8. Drive the engine at 4500 RPM for 10 minutes. 9. Drive the engine at 5000 RPM for 10 minutes. 10. Drive the engine at 5500 RPM for 10 minutes.

- ✓ Check the oil level and change it if necessary.
- ✓ Check the spark plug gap and adjust it if necessary.
- ✓ Check the air filter and clean it if necessary.
- ✓ Check the fuel filter and replace it if necessary.
- ✓ Check the battery and charge it if necessary.
- ✓ Check the belt tension and adjust it if necessary.
- ✓ Check the cooling system and fill it with water if necessary.
- ✓ Check the exhaust system and clean it if necessary.
- ✓ Check the engine oil and change it if necessary.

## 600 Mile Checkup:

- ✓ Check the oil level and change it if necessary.
- ✓ Check the spark plug gap and adjust it if necessary.
- ✓ Check the air filter and clean it if necessary.
- ✓ Check the fuel filter and replace it if necessary.
- ✓ Check the battery and charge it if necessary.
- ✓ Check the belt tension and adjust it if necessary.
- ✓ Check the cooling system and fill it with water if necessary.
- ✓ Check the exhaust system and clean it if necessary.
- ✓ Check the engine oil and change it if necessary.

